

SL

Silent Oil Free Scroll Air Compressor

- 100% Oil Free, Ideal For Food Processing and Applications that require Oil Free Air
- Highly Efficient and Silent
- Simple Maintenance
- No Hazardous Exhaust
- Compact Size

High Efficiency IE4 Motor



Scroll Compression Diagram



SL-30



SL-30



SL-75T2-AD



SL-50



SL-50

Model	Power		Max Working Pressure	FAD	Tank Volume	Noise	Dimensions			Air Outlet Size	Weight	Air Tank	Air Dryer
	HP	kW	bar	L/min	L	dB (A)	mm	mm	mm	inch	kg		
SL-30	3	2.2(2.2*1)	8~10	240	/	58±2	640	660	890	1/2"	200		
SL-50	5	3.7(3.7*1)	8~10	420	/	58±2	640	660	890	1/2"	220		
SL-75	7.5	5.5(5.5*1)	8~10	620	/	58±2	640	660	890	3/4"	240		
SL-30T	3	2.2(2.2*1)	8~10	240	24	58±2	960	660	1360	1/2"	210	✓	
SL-50T	5	3.7(3.7*1)	8~10	420	24	58±2	960	660	1360	1/2"	230	✓	
SL-75T	7.5	5.5(5.5*1)	8~10	620	24	58±2	960	660	1360	3/4"	250	✓	
SL-75T2	7.5	5.5(5.5*1)	8~10	620	200	58±2	1340	650	1530	3/4"	290	✓	
SL-30T-AD	3	2.2(2.2*1)	8~10	240	24	58±2	960	660	1360	1/2"	260	✓	✓
SL-50T-AD	5	3.7(3.7*1)	8~10	420	24	58±2	960	660	1360	1/2"	350	✓	✓
SL-75T-AD	7.5	5.5(5.5*1)	8~10	620	24	58±2	960	660	1360	3/4"	320	✓	✓
SL-75T2-AD	7.5	5.5(5.5*1)	8~10	620	200	58±2	1340	650	1530	3/4"	370	✓	✓

Unoair 全無油渦卷式空氣壓縮機

SL

全無油渦卷式空氣壓縮機

100% 無油，適合食物加工和其他嚴格要求無油的用途


無有害排放物

簡單保養

極低噪音

小體積，操控簡易

高效率省電IE4馬達



渦卷壓縮示意圖



SL-30



SL-30



SL-75T2-AD



SL-50



SL-50

型號	功率		工作壓力	排氣量	壓力容器容量	噪音值	空壓機體積			出氣口尺寸	總重量	含壓力容器	含乾燥機
	HP	kW	bar	L/min	L	dB (A)	mm	mm	mm	inch	kg		
SL-30	3	2.2 (2.2*1)	8~10	240	/	58±2	640	660	890	1/2"	200		
SL-50	5	3.7 (3.7*1)	8~10	420	/	58±2	640	660	890	1/2"	220		
SL-75	7.5	5.5 (5.5*1)	8~10	620	/	58±2	640	660	890	3/4"	240		
SL-30T	3	2.2 (2.2*1)	8~10	240	24	58±2	960	660	1360	1/2"	210	✓	
SL-50T	5	3.7 (3.7*1)	8~10	420	24	58±2	960	660	1360	1/2"	230	✓	
SL-75T	7.5	5.5 (5.5*1)	8~10	620	24	58±2	960	660	1360	3/4"	250	✓	
SL-75T2	7.5	5.5 (5.5*1)	8~10	620	200	58±2	1340	650	1530	3/4"	290	✓	
SL-30T-AD	3	2.2 (2.2*1)	8~10	240	24	58±2	960	660	1360	1/2"	260	✓	✓
SL-50T-AD	5	3.7 (3.7*1)	8~10	420	24	58±2	960	660	1360	1/2"	350	✓	✓
SL-75T-AD	7.5	5.5 (5.5*1)	8~10	620	24	58±2	960	660	1360	3/4"	320	✓	✓
SL-75T2-AD	7.5	5.5 (5.5*1)	8~10	620	200	58±2	1340	650	1530	3/4"	370	✓	✓